

中部沖繩トラフクメ島沖熱水活動域におけるAUV「うらしま」潜航調査

Acoustic and magnetic surveys using AUV Urashima around the hydrothermal sites off Kumejima island in the Mid-Okinawa Trough

*北田 数也¹、中村 謙太郎²、高橋 亜夕³、川口 慎介⁴、熊谷 英憲¹

*Kazuya Kitada¹, Kentaro Nakamura², Ayu Takahashi³, Shinsuke Kawagucci⁴, Hidenori Kumagai¹

1.海洋研究開発機構海底資源研究開発センター、2.東京大学大学院工学系研究科システム創成学専攻、3.海洋研究開発機構次世代海洋資源調査技術研究開発プロジェクトチーム、4.海洋研究開発機構深海・地殻内生物圏研究分野

1.Research and Development Center for Submarine Resources, Japan Agency for Marine-Earth Science and Technology, 2.Department of Systems Innovation, School of Engineering, University of Tokyo, 3.Project Team for Development of New-generation Research Protocol for Submarine Resources, Japan Agency for Marine-Earth Science and Technology, 4.Department of Subsurface Geobiological Analysis and Research, Japan Agency for Marine-Earth Science and Technology

Recently, polymetallic sulfides deposited in seafloor hydrothermal vents have attracted interest as a potential mineral resources for e.g., Cu, Zn, Pb, In, Ga, Ge, Au, and Ag (Schrope, 2007).

Development of effective methods for exploring seafloor hydrothermal activity is an important key for future exploitation of this type of deep-sea mineral resource and thus, more efficient methods for exploration of seafloor hydrothermal vents are expected.

Recent progress in near-bottom geophysical and geochemical surveys using autonomous underwater vehicles (AUV) allows us to perform high-resolution surveys in which the signatures of seafloor hydrothermal activity can be detected (German et al., 2008; Kumagai et al., 2010; Nakamura et al., 2013). Moreover, in the last decade, water column observations using multi-beam echo sounder (MBES) systems equipped on a surface ship have also become successfully applied to exploration of seafloor hydrothermal vents (Tanahashi et al., 2014; Kasaya et al., 2015; Nakamura et al., 2015).

During the YK15-14 cruise in 2015, we conducted the shipboard MBES survey by R/V "Yokosuka" and the near-bottom acoustic and magnetic surveys using AUV "Urashima" around the hydrothermal sites in order to reveal the distribution and characteristics of seafloor hydrothermal vent sites off Kumejima island in the mid-Okinawa Trough. The presence and amplitude of hydrothermal plume signals were first detected by acoustic water column imaging with a shipboard MBES system. A total of four AUV "Urashima" dives (Dives #217-220) were completed around the sites. During these dives, we have successfully obtained high-resolution bathymetric data, side scan sonar image, sub-bottom profile, vector magnetic field and chemical sensor data (ORP, turbidity and temperature). The vector magnetic field were measured by three fluxgate magnetometers mounted in the payload space of AUV "Urashima" to investigate the seafloor magnetic features related to hydrothermal alteration processes. The distribution of crustal magnetization are estimated using the magnetic anomalies by the inversion method. Here we report the overview of the YK15-14 cruise and show new results from AUV "Urashima" dives. Then, the characteristics of the hydrothermal sites in the mid-Okinawa Trough will be discussed by comparing with the results from the ROV surveys during the KR15-16 cruise.

キーワード：海底熱水探査、中部沖繩トラフ、AUV、詳細海底地形、磁気異常

Keywords: seafloor hydrothermal exploration, mid-Okinawa Trough, AUV, detailed bathymetry, magnetic anomaly