

[EE] Evening Poster | A (Atmospheric and Hydrospheric Sciences) | A-HW Hydrology & Water Environment

## [A-HW22]Hydrological Cycle and Water Environment

convener:Seiya Nagao(Institute of Nature and Environmental Technology, Kanazawa University), Isao Machida(Geological Survey of Japan), Shin'ichi Iida(国立研究開発法人森林研究・整備機構森林総合研究所森林研究部門森林防災研究領域水保全研究室, 共同), Takeshi Hayashi(Faculty of Education and Human Studies, Akita University)

Thu. May 24, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

We focus on various issues of water cycle and environment and aim to answer questions of hydrological and earth system sciences including 1) surface, subsurface and evapotranspiration processes of water cycle; 2) natural and anthropogenic hydrothermal systems, 3) environments issues and studies on a watershed or global scale, 4) water-related issues with ecological, environmental, and geochemical aspects, and 5) other issues in hydrological sciences. This session welcomes presentations regarding various kinds of approaches and techniques such as field survey, remote sensing, isotope tracers, numerical simulation, and theoretical analysis.

## [AHW22-P06]Fusion of Time-Lapse Gravity Survey and Hydraulic Tomography for Estimating Spatially Varying Hydraulic Conductivity and Specific Yield Fields

\*Jui-Pin Tsai<sup>1</sup>, Liang-Chang Chang<sup>1</sup>, Tian-Chyi Jim Yeh<sup>2</sup> (1.National Chiao-Tung University, Taiwan , 2.The University of Arizona, USA)

Keywords:Hydrogeological parameters, Gravity, Hydraulic tomography, Joint interpretation

Hydraulic conductivity ( $K$ ) and specific yield ( $S_y$ ) are important aquifer parameters, pertinent to groundwater resources management and protection. These parameters are commonly estimated through a traditional cross-well pumping test. Employing the traditional approach to obtain detailed spatial distributions of the parameters over a large area is generally formidable. For this reason, this study proposes a stochastic method that integrates hydraulic head and time-lapse gravity based on hydraulic tomography (HT) to efficiently derive the spatial distribution of  $K$  and  $S_y$  over a large area. This method is demonstrated using several synthetic experiments. Results of these experiments show that the  $K$  and  $S_y$  fields estimated by joint inversion of the gravity and head dataset from sequential injection tests in unconfined aquifers are superior to those from the HT based on head data alone. We attribute this advantage to the mass constraint imposed on HT by gravity measurements. Besides, we find that gravity measurement can detect the change of aquifer's groundwater storage at kilometer scale, as such they can extend HT's effectiveness over greater volumes of the aquifer. Furthermore, we find that the accuracy of the estimated fields is improved as the number of the gravity stations is increased. The gravity station's location, however, has minor effects on the estimates if its effective gravity integration radius covers the well field.