
[EE] Eveningポスター発表 | セッション記号 A (大気水圏科学) | A-HW 水文・陸水・地下水学・水環境

[A-HW22]水循環・水環境

コンビナー:長尾 誠也(金沢大学環日本海域環境研究センター)、町田 功(産業技術総合研究所地質調査総合センター)、飯田 真一(国立研究開発法人森林研究・整備機構森林総合研究所森林研究部門森林防災研究領域水保全研究室、共同)、林 武司(秋田大学教育文化学部)

2018年5月24日(木) 17:15 ~ 18:30 ポスター会場 (幕張メッセ国際展示場 7ホール)

本セッションでは、主に地球科学の視点で水循環・水環境に関連する分野を横断的に連携し、総合的な解析や評価手法を構築することを目指している。具体的には、地下水・湖水・地表水・蒸発散・熱水系といった水循環のプロセス研究、流域や地域、地球規模の環境問題を扱う水環境の研究、水に係わる生態環境科学的、地球化学的視野に立つ研究、その他の水文学的な研究が含まれる。

[AHW22-P12]A Multi-Objective Optimization formulation for transient flow restriction in Wellhead Protection

*Abelardo Rodriguez Pretelin¹、Wolfgang Nowak¹ (1.Institute for Modelling Hydraulic and Environmental Systems (IWS), University of Stuttgart, Stuttgart, Germany)

キーワード : Wellhead Protection Area, Transient groundwater analysis, Multiobjective Optimization

Groundwater is typically obtained via drinking water wells. To ensure safety and sustainable supply conditions, most groundwater protection programs restrict land use within the zone of groundwater abstraction that have the potential to contaminate the groundwater. The delineation of such wellhead protection areas (WHPAs) is commonly based on the use of groundwater models under the assumption of steady-state flow conditions. Despite this assumption transient groundwater flow can exert significant variation on the actually required WHPA outline. For example, during consecutive periods of warm and rainy seasons, pumping wells might increase and decrease their water abstraction, respectively. This, combined with changes in the mean ambient groundwater flow caused by same dynamic weather environment (e.g., changes in the regional flow direction or the regional hydraulic gradient) might trigger a variation over time of the water abstraction zone of the well. This can lead to a risk scenario, where locations with dangerous land use conditions (e.g., gas stations or agricultural lands) might be actually included within the abstraction zone, during particular time intervals.

The goal of this study is to present a novel pumping-injection management scheme that reduces the influence of transient flow conditions on the actual abstraction zone, so that abstraction remains within the delineated WHPA. Thus, steady-state WHPAs together with old schemes can represent a robust solution against dynamic environments. To formulate our management approach, we use multi-objective optimization (MOO) concepts, searching for compromise solutions that consider at least three objectives: 1) to minimize the risk of pumping water from outside of a given WHPA, 2) to maximize groundwater supply and 3) to minimize involved costs. Additionally, given the high computational cost attributed to dynamic MOO solutions, we explore and analyze a suboptimal alternative where the computed set of non-dominant solutions remain constant for longer time periods. This, provides a more stable well management operation, while skipping many time steps in the optimization.

With the presented framework, we aim to provide to decision makers well operation alternatives that reduce the impact of transiency while considering additional management issues in well catchment protection.