
[EJ] Evening Poster | A (Atmospheric and Hydrospheric Sciences) | A-HW Hydrology & Water Environment

[A-HW23]Residence time of groundwater / surface water and water / mass cycle processes in watershed

convener:Maki Tsujimura(Faculty of Life and Environmental Sciences, University of Tsukuba), Shigeru Mizugaki(PWRI Public Works Research Institute), Masanori Katsuyama(京都大学農学研究科, 共同), Maksym Gusyev(International Centre for Water Hazard Risk Management, Public Works Research Institute)
Thu. May 24, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

The residence time of ground/ surface water is one of the most important parameters to understand hydrological and mass cycle processes in a watershed. However, residence time information of the water is still lacking to characterize watersheds with steep topography underlain by young lithology, with a special concern of soil / gravel discharge, solute transport and hydro-geomorphological processes. Generally, we investigate the residence time of the water by applying radionuclides / noble gas tracers showing apparent age as ^3H , ^{36}Cl , CFCs and SF_6 , and/ or conservative tracers like stable isotopes, and need to understand a difference of residence time estimated by different type of tracers in various hydro-geological settings.

In this session, we compare the residence time of ground/ surface water and mass transport processes observed in various types of the watershed, and discuss issues to be solved and future perspectives on water age and mass cycle research topics.

[AHW23-P01]Validity of discharge and parameters associated with groundwater in the hydrological model SWAT for the Mukawa River and the Saru River, northern Japan

*Shigeru Mizugaki¹, Atsushi Tanise¹, Ryuichi Shimme¹ (1.Civil Engineering Research Institute, Public Works Research Institute)

Keywords:Soil and Water Assessment Tool (SWAT), groundwater delay time, discharge

Prediction of water, sediment and nutrients discharge is important in assessing the impact of climate change and land use on watershed and coastal environments. SWAT (Soil and Water Assessment Tool) is one of the hydrological model platforms to simulate the dynamics of water, soil erosion, nutrient for agricultural land basin developed by the US Department of Agriculture (USDA). While there is an advantage that can be used for future prediction by a quasi-physical model in which the hydrological process is taken into consideration, difficulty is often accompanied by adjustment of enormous parameters. Therefore, it is important to reduce the number of indefinite parameters and consider the validity of the adjusted value by using the on-site information and observation data as much as possible, likely to contribute to improvement of model. In this study, we collected the local soil survey data and created a soil database for SWAT, and attempted to simulate the daily discharge in the Mukawa and Saru River basins. In the results of parameter tuning for 3 years (2010-2012), significantly high similarity was obtained with high Nash-Sutcliffe efficiency (NS) of 0.78 and 0.79 for the Mukawa River and Saru River, respectively. In order to confirm the validity of the parameter set, the simulated discharge was compared to observed data for each seven subcatchments, showing good estimations that the NS values ranged from 0.56 to 0.72, R^2 ranged from 0.66 to 0.81, and the similarity in total runoff for 3 years ranged from 78% to 100%. Among the 18 parameters obtained in this study, such groundwater-associated parameters as groundwater delay time was found to be significant for better simulation by sensitivity analysis. For better simulation of discharge in various subcatchments, mean

transit time or residence time of groundwater estimated by such tracers as tritium, stable isotope or CFCs could be incorporated in the parameters to reduce the number of parameters and take into account the scale effect and spatial variability of underlying geology.