
[JJ] Evening Poster | H (Human Geosciences) | H-DS Disaster geosciences

[H-DS10]Tsunami and Tsunami Forecast

convener:Naotaka YAMAMOTO CHIKASADA(National Research Institute for Earth Science and Disaster Resilience), Kentaro Imai(Japan Agency for Marine-Earth Science and Technology), Hiroaki Tsushima(気象庁気象研究所)

Wed. May 23, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

This session discusses issues related to improving real-time and long-term prediction accuracy of tsunami from earthquakes, landslides, and volcanoes, which include such as a better understanding of tsunami dynamics, new real-time tsunami observing systems deployed in the open ocean and coastal waters, methodologies of more rapid and accurate prediction during tsunami emergencies, more extensive and accurate inundation maps, and long-term tsunami potential forecast.

[HDS10-P15]Comparisons between Boussinesq type and numerical error models in far-field dispersive tsunami calculation

*Kimura Kengo¹ (1.Department of Civil and Environmental Engineering The University of Tokushima)

Keywords:far-field tsunami, dispersion

We should consider frequency dispersion for the calculation of far-field tsunami. To take the dispersion effect into account in numerical simulation, Boussinesq (dispersion) term is often added to the shallow water equations. Solving the dispersion term requires an implicit method with high computational cost. On the other hand, a numerical error model also simulates the dispersion phenomena treating discretization error in the difference equations as the physical dispersion term so that the implicit method is not needed. However, the numerical error model determines grid interval and time step to be term of the discretization error corresponding the physical dispersion term. For far-field tsunami, optimized grid interval is about 5arc-min which would be too coarse to investigate the detail nature of dispersion. In this study, we compared tsunami waveforms calculated by the Boussinesq type model and ones by the numerical error model to discuss prediction accuracy and computational efficiency. For the calculation using the Boussinesq type model, the grid interval was set to be 0.5 arc-min to suppress the discretization error. For the numerical error model, the grid interval of 5 arc-min was used to match the discretization error to the physical dispersion. We calculated tsunami generated by the 2011 Tohoku earthquake for 28 hours. Calculated tsunami waveforms from the two models were compared at DART stations over the Pacific Ocean. The comparisons indicated that there is no significant difference between the tsunami waveforms from the two models for the leading waves. But, at the stations near the earthquake source, the water level of the later waves is greatly different. The Boussinesq type calculation and the numerical dispersion model took about 151 hours and only 18 minutes, respectively, to finish the calculation.