
[JJ] Evening Poster | H (Human Geosciences) | H-SC Social Earth Sciences & Civil/Urban System Sciences

[H-SC05]CCUS (Carbon Dioxide Capture, Utilization, and Storage) for Climate Mitigation

convener: Masao Sorai (Institute for Geo-Resources and Environment, National Institute of Advanced Industrial Science and Technology), Ziqiu Xue (Research Institute of Innovative Tech for the Earth), Masaatsu Aichi (東京大学大学院新領域創成科学研究科)

Wed. May 23, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

The prevention of the global warming, which is the urgent challenge facing the world, requires the full-out efforts of science and technology. This session focuses on the CCUS (Carbon Dioxide Capture, Utilization, and Storage) as one of the useful countermeasures for the CO₂ emission reduction. It not only targets various scientific phenomenon caused by the capture and storage of CO₂, CO₂ utilization, and CO₂-EOR/EGR, but also discusses the latest R&D developments of each method for the environmental impact assessment, safety assessment, the measuring, monitoring and verification (MMV), and public acceptance.

The main theme is the recognition of key issues toward the practical use of CCUS, in addition to the deepening of our knowledge about the CO₂ behavior on the underground.

[HSC05-P02] Application of sequentially discounting autoregressive (SDAR) on seismic event detection for CO₂ injection safety management

*Luchen Wang¹, Tetsuma Toshioka¹, Takahiro Nakajima¹, Akira Narita², Ziqiu Xue¹ (1.RITE Research Institute of Innovative Technology for the Earth, 2.Mitsubishi Space Software Co., Ltd.)

When injecting fluid into the deep formations or reservoirs, a big concern is the potential induced micro-seismic events. An earthquake-based monitoring system, called Traffic Light System (TLS), has already been applied to evaluate the micro-seismic events and manage the fluid injection (e.g. the geothermal exploration and the shale gas development). As injecting CO₂ is similar to fluid, the similar system can also be employed to automatically evaluate the CO₂ injecting situation and inform the anomaly for injection safety management. For the application at regions with frequent natural earthquakes (e.g. the CCS site at Tomakomai, Japan), we are developing an Advanced Traffic Light System (ATLS) to achieve self-adaptive seismic monitoring and injection management. Combining the baseline seismicity information and the seismic behavior of aftershock, the ATLS can provide valuable information of the induced seismic events.

The primary task for ATLS management is the micro-seismic event identification in a long-term sustained time series. It is a challenge for ATLS to detect such weak energy seismic signal with potential low Signal to Noise Ratio (SNR). In order to optimize the effect of ATLS seismic monitoring, a high-sensitivity micro-seismic detection method is necessary. In this study, the Sequentially Discounting AutoRegressive (SDAR) method is applied for seismic event detection. Considering that the seismic observation data is a stochastic time series consisting of valid seismic event signal and random noise, the SDAR method assumes that the segments between earthquake and noise are stationary as different autoregressive statistical models. Since the SDAR method avoids the signal energy calculation, it can work on weak seismicity identification, especially micro-seismic events.

Here we apply the SDAR method on the Ocean Bottom Cable (OBC) baseline recording at Tomakomai CCS project for natural earthquake detection. The corresponding data was observed from Feb. 1st 2015 to Jan. 31st 2016. The earthquake detection result confirms that the SDAR is a feasible and robust tool for

earthquake detection in long-term time series record, especially for micro-seismic events (magnitude <1) at CCS site. Near Tomakomai CCS site, only weak earthquakes (magnitude <2) occurred during the baseline period. This detecting result can be used by ATLS to obtain the background seismic activity information.