

---

 [JJ] Evening Poster | M (Multidisciplinary and Interdisciplinary) | M-TT Technology & Techniques

## [M-TT38] Brand-new scope of coupling geophysics being established by infrasound and associated waves

convener: Masa-yuki Yamamoto (Department of systems engineering, Kochi University of Technology), Nobuo Arai (Disaster Mitigation Research Center, Nagoya University), Mie Ichihara (東京大学地震研究所)  
 Sun. May 20, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

Infrasound and associated wave studies are recently focused on coupling waves with long-distance and vertical propagation characteristics. Such kinds of waves, having with coupling process between the atmosphere and the surface of ground and ocean, are linked with elastic waves in lithosphere and oceanic sphere, as well as to atmospheric regions up to the upper atmosphere, playing a role of generating many kinds of wavelike turbulences in thermosphere. Moreover, whole on the globe, these waves excited depending on the latitude regions, as well as on the environmental regions, such as snow ice, desert, rainforest, mountain, ocean, etc., have their own characteristics. These waves can be excited by large-scale geophysical events like volcanic eruptions, tsunami, thunderstorms, etc. as well as artificial explosions, propagating with long distance. In this session, we would like to discuss such "coupling geophysics" by using many new or well-known investigated data and simulations of infrasound and associated low frequency waves. It can combine multiple spheres in geophysics and bring a brand-new scope of geophysics. Your contributions from many regions are welcome!

---

## [MTT38-P05] Development of the sound source exploration technique using plural small Rover in the Mars exploration

\*Yuki Otsuka<sup>1</sup>, Hiroaki Saito<sup>1</sup>, Masa-yuki Yamamoto<sup>1</sup> (1.Kochi University of Technology)

Keywords: Sound source exploration, Mars, Several small rovers, Infrasound

### Introduction

In Mars explorations so far, two or more rovers have never been explored at the same time and spot. In addition, the sound on Mars, for example, the sound of sandstorm, volcanic eruption, mostly have not been observed by previous Mars explorations.

Therefore, in this study, the systems is developed for Mars explorations by using several small rovers. And The purpose of this system is the observation of the sound on Mars. If this system can be implemented, we can measure many kinds of physical quantities indirectly.

### Searching sound source

Several slave rovers have microphones and search sound source. The master rover gathers and processes information from slave rovers, grasps location information of slave rovers and communicates with the ground station or relay satellite. The details of the method for probing Mars are as follows. After landing on Mars, three slave rovers form an equilateral triangle centered around the master rover. By forming an equilateral triangle, the directivity of this system can be eliminated. During searching sound source, this system uses infrasound. Therefore, the distance between each slave rovers is from 30m to 50m. In this case, this system can cover about 4.6Hz to 7.7Hz. Infrasound results from aerial vibration caused by the release of gas or thunder. As described above, this system can observe the release of gas or sandstorm on Mars by using infrasound.

When searching the sound source, this system estimates a position of sound source by cross-correlation function on the sound waveform that each microphone measured. Regarding signal-f received by microphone1 and signal-g received by microphone2, when shifting signal-g by n samples.

### **Sound source position estimate experiment**

It is conducted two experiments using three IC recorders and three original recording devices. In each experiment, it is formed IC recorders or original recording devices in an equilateral triangle. After that, we made sound from arbitrary point. Conducting cross-correlation function on each recorded wave data, time difference of arrival and distance difference from the sound source was found. We created hyperbolas by using distance difference between the sound source and drew the locus of the candidate for sound source position.

### **Results and consideration**

The result of experiments by using IC recorder are shown in figure 1. The results of experiment by using original recording devices are shown in figure 2.

In the experiment by using IC recorders, the sound source position was estimated precisely. However in the experiment by using original recording devices, sound source position was not found. Because of noise caused by wind, an error occurs in the result of cross-correlation processing. It is required for solving this problem to deal with error covering microphones with the sponge.

### **Conclusion**

Our program for estimating sound source position operated normally. However this original recording devices are weaker than noise caused by wind. After solving this problem, further study is needed for autonomous operation of rovers, master rovers and so on.