[JJ] Evening Poster | S (Solid Earth Sciences) | S-CG Complex & General

[S-CG64]Brittle-Ductile Transition and Supercritical Geofluids for Crustal Energy in Island Arc

convener:Noriyoshi Tsuchiya(Graduate School of Environmental Studies, Tohoku University), Hiroshi Asanuma(AIST), Yasuo Ogawa(東京工業大学理学院火山流体研究センター)

Mon. May 21, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe) Nature of rock mass below the brittle-ductile transition (BDT) is of great scientific interest to understand various phenomenon in the Earth's crust. We will review and discuss current understanding of characteristics the rock mass below the BDT, including composites, stress, failure mechanism induced by liquid injection and associates earthquake generation mechanism, and water rock interaction, considering engineered geothermal development in the BDT. Discussions on the possible phenomena in the geothermal development in the BDT will be followed in this session.

New drilling technology is key of issues. This session will cover advanced drilling technology under high temperature conditions for energy extraction.

[SCG64-P06]Effects of temperature, pressure and NaCl concentration on electrical conductivity of geothermal fluid using molecular dynamics

*Makoto Enokimaru¹, James Cannon², Kazuki Sawayama³, Keigo Kitamura⁴, Yasuhiro Fujimitsu⁵ (1.Graduate school of engineering, Cooperative Program for Resources Engineering, Kyushu University, 2.Faculty of Engineering, Department of Mechanical Engineering, Kyushu University, 3.Graduate school of engineering, Department of Earth Resources Engineering, Kyushu University, 4.International Institute of Carbon Neutral Energy Research, Kyushu University, 5.Faculty of Engineering, Department of Earth Resource Engineering, Kyushu University)

Keywords:electrical conductivity, molecular dynamics, geothermal fluid, magnetotellulic

Understanding the behavior of geothermal fluid is important to achieve the sustainable resource development. Generally, the geothermal fluid behavior is evaluated by geophysical explorations such as Magnetotellurics (MT method). MT method is one of the electromagnetic explorations estimating the subsurface structure from the resistivity distribution under the ground. This method is generally used for understanding the distribution of geothermal fluid because its resistivity is low. It is well known that the electric properties of NaCl fluid depend on temperature, pressure, and ionic concentration of NaCl solution. For the quantitative interpretation of water distribution from resistivity profile illustrated by MT method, it is necessary to investigate the effects of temperature, pressure, and ionic concentration of NaCl solution on the electrical conductivity of the fluid. under geothermal reservoir conditions (hereafter GR situation) However, the existing experimental and simulated data for electrical conductivity of fluid are not insufficient to evaluate these effects on the electrical conductivity of geothermal fluid under GR situation. The goal of this study is to investigate electrical conductivity of NaCl fluid under GR situation to interpret water distribution of geothermal fluid quantitatively. In this study, we investigated electrical conductivity under temperature, pressure and NaCl concentration of 400-600 K, 5-30 MPa and 0.3-2.0 mol/L, respectively. Since it is difficult to measure the electrical conductivity of NaCl fluid under GR situation, we employed molecular dynamics (MD) simulation to estimate electrical conductivity of NaCl fluid. Our calculation used LAMMPS(ver.2017) for MD simulation and the Green-Kubo relations for estimation of electrical conductivity from calculated results by MD

simulation. We confirmed the validities of our simulation results by comparing with existing experimental results. As a result, a strong dependence of electrical conductivity on temperature was confirmed. Electrical conductivity increases with temperature and it shows the peak around 550 K of temperature. After this peak, electrical conductivity decreases with the increment of temperature. In the case of 1.0 mol/L of NaCl concentration and 30 MPa of pressure condition, comparing 400K of temperature with 550K of the peak temperature, electrical conductivity increases about 9.2 S/m. At 600 K of temperature, which is after the peak temperature, electrical conductivity decreases 0.8 S/m. These trends are consistent with previous experimental results. Meanwhile, the pressure dependence of electrical conductivity was not confirmed in GR situation in our calculated results (1.4%). Our simulation results indicate that NaCl concentration has the largest effect on the electrical conductivity of the three parameters as temperature, pressure and NaCl concentration under GR situation. In the case of 500 K of temperature and 30 MPa of pressure condition. The database of electrical conductivity of NaCl fluid under GR situation in this study is expected to contribute to the more precise interpretation of the electromagnetic exploration.