

---

 [JJ] Evening Poster | S (Solid Earth Sciences) | S-CG Complex & General

## [S-CG67] Ocean area observation to detect crustal activity under the seafloor: Present and future

convener: Kazuro Hirahara (Department of Geophysics, Earth and Planetary Sciences, Graduate School of Sciences, Kyoto University), Ryota Hino (Graduate School of Science, Tohoku University), Takane Hori (独立行政法人海洋研究開発機構・地震津波海域観測研究開発センター)

Thu. May 24, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

Recent progress of seafloor observations for earthquake and crustal deformation, such as deployment of submarine cable networks of S-net and DONET, and repeated observations of GNSS/A and acoustic extensometer (direct path acoustic ranging), enable us to evaluate on-going crustal activities in the megathrust regions along the Japan trench and the Nankai trough. We review the present status and the future plans of such seafloor observations, and discuss the future directions of seafloor observation networks, especially for real-time monitoring of crustal activities. Toward these directions, we welcome papers introducing the present status of novel approaches and systems such as optical fiber, laser ranging or seafloor SAR and real-time geodetic observations using mooring buoys or wave glider, and so on. We also welcome future plans to integrate observation for the crustal activity under the seafloor with observation for ocean and climate changes.

---

## [SCG67-P02] Array positioning analysis of GPS-Acoustic observation data considering lateral gradient of the sound speed in seawater

\*Chie Honsho<sup>1</sup>, Motoyuki Kido<sup>2</sup>, Fumiaki Tomita<sup>1</sup> (1. Graduate School of Science, Tohoku Univ., 2. IRIDeS, Tohoku Univ.)

Keywords: GPS-A observation, Lateral gradient of the sound speed in seawater

In each geodetic benchmark on the seafloor for GPS-Acoustic observation, 3~6 precise precision transponders (PXPs) are settled to form a triangular or square array. The array positioning is an analysis to determine array displacements assuming that relative positions between the PXPs are unchanged, i.e. the array moves rigidly [e.g., Spiess et al., 1998]. One of the most important parameters in the analysis is the sound speed in seawater. Usually, a reference profile of the sound speed, which is a function of water depth, is constructed based on oceanographic observations such as Conductivity-Temperature-Depth (CTD) measurements, and then small fluctuation of the sound speed structure is solved together with the array displacement. We, the Tohoku University group, have used a quantity called ‘Nadir Total Delay (NTD)’ to represent the fluctuation of the sound speed [e.g., Kido et al., 2006; Honsho & Kido, 2017]. The NTD is analogous to ‘Zenith Total Delay’ in the GNSS analysis and defined as a vertically normalized traveltimes residual, i.e. a difference between observed and synthetic traveltimes normalized onto a hypothetical vertical path according to the slant of the acoustic path. When a laterally stratified structure is assumed for the sound speed, the NTD is a function of time only and independent of an azimuth and an emission angle of the acoustic path. Then, we have adopted a method in which the time variation of the NTD and the array position are solved simultaneously.

The assumption of laterally stratified structure is primarily valid. However, there are lateral variations in actual, which can result in systematic errors as much as several centimeters in the array positioning. In this study, we consider a lateral gradient of the sound speed as a first-order approximation of lateral variations. Then, we introduce an array positioning method considering the gradient and report the results of its application to actual data.

We can obtain two kinds of information on the gradient from traveltimes data. First, the gradient and the array displacement give changes to traveltimes in different manners; therefore, they can be theoretically distinguished using traveltimes data with various emission angles. Second, the NTD variation observed while a ship moves around above the array often shows a distribution which seems to be related to the ship positions. One example is the case where the NTDs observed when the ship is located in the north of the array are generally larger than those in the south of the array; this may indicate that the sound speed is generally smaller in the north than in the south. The above two kinds of information, however, have disadvantages respectively. As for the former, the effects of the gradient and array displacement on traveltimes are different but quite similar, and thus the results can be easily affected by data or modeling errors. As for the latter, the NTD variation that is observed while the ship moves around cannot be distinguished as a temporal or spatial variation in principle.

From numerical experiments and analyses using actual data, we concluded that more reasonable results were obtained when both kinds of information were utilized together, rather than using either of them. Then, we applied the analysis considering the gradient to the actual data obtained from ~120 campaigns conducted during 2012–2016 at the 20 observation sites off the Tohoku region. Some artificial, zig-zag movements of horizontal array position recognized in the previous results [Tomita et al., 2017] tend to be suppressed. Accordingly, the estimated displacement rates were slightly changed and showed more similar rates among neighboring sites.

It remains an issue of the method how the depth of the fluctuating layer, which has significant effects on the results, is chosen. It is tentatively set to 500 m for several reasons, but each of them lacks a decisive ground. We will continue discussions on the matter in the future.