[JJ] Evening Poster | S (Solid Earth Sciences) | S-CG Complex & General

[S-CG67]Ocean area observation to detect crustal activity under the seafloor: Present and future

convener:Kazuro Hirahara(Department of Geophysics, Earth and Planetary Sciences, Graduate School of Sciences, Kyoto University), Ryota Hino(Graduate School of Science, Tohoku University), Takane Hori(独立行政法人海洋研究開発機構・地震津波海域観測研究開発センター)

Thu. May 24, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe) Recent progress of seafloor observations for earthquake and crustal deformation, such as deployment of submarine cable networks of S-net and DONET, and repeated observations of GNSS/A and acoustic extensometer (direct path acoustic ranging), enable us to evaluate on-going crustal activities in the megathrust regions along the Japan trench and the Nankai trough. We review the present status and the future plans of such seafloor observations, and discuss the future directions of seafloor observation networks, especially for real-time monitoring of crustal activities. Toward these directions, we welcome papers introducing the present status of novel approaches and systems such as optical fiber, laser ranging or seafloor SAR and real-time geodetic observations using mooring buoys or wave glider, and so on. We also welcome future plans to integrate observation for the crustal activity under the seafloor with observation for ocean and climate changes.

[SCG67-P06]Development of acoustic signal processing unit for continuous observation of ocean bottom crustal deformation using marine GNSS buoy

*Natsuki Kinugasa¹, Keiichi Tadokoro¹, Shun Inagaki¹, Yukihiro Terada³, Akira Futamura⁴, Teruyuki Kato² (1.Graduate School of Environmental Studies, Nagoya University, 2.Earthquake Research Institute, the University of Tokyo, 3.National Institute of Technology, Kochi College, 4.National Institute of Technology, Yuge College)

Keywords:Ocean bottom crustal deformation, GPS/Acoustic method, Marine GNSS buoy

Observation for ocean bottom crustal deformation by global navigation satellite system (GNSS) /acoustic method is monitoring long-term changes in the position of transponder which is estimated from the travel time of acoustic signal between onboard transducer and transponder fixed on seafloor. Observation using vessel can be performed only several times a year and provides low temporal resolution for measurements. That is a problem for monitoring the time variation of fixing strength of plate boundary. It is expected that continuous observation helps to clarify the mechanisms of slow slip events, which take place along the plate interface, in more detailed.

We aim to realize continuous observation by using marine buoy. The Grant-in-Aid for Scientific Research (S) project " A challenge to develop GNSS buoy system for high-functional tsunami monitoring and continuous observation of ocean-bottom crustal movements" which has been started from 2016 utilizes the buoy off the coast of Ashizuri. It is equipped with GNSS (global navigation satellite system) antenna and receiver, acoustic ranging unit, and satellite communication unit. From buoy to ground station, the satellite communication unit transfers the results of acoustic ranging, and the position of buoy, which is estimated by precise point positioning. Our acoustic ranging system consists of acoustic ranging and signal processing devices which are connected with each other through USB cables. When the signal processing device receives the acoustic signal, it executes the correlation processing and outputs

the messages including transmitted time and travel time to the satellite communication unit.

The accurate travel time can be obtained by correlation processing between replica and received acoustic signals. When the signal is reflected by sea surface, several peaks appear in the correlation coefficient. The result of observation using vessel shows that the correlation value peak of reflected signal was sometimes larger than that of direct signal. In this case, the peak position of direct signal exists former than the maximum peak position because a direct signal arrives primarily. That also suggests that the amplitude of received signal increases sharply at the timing of its arrival.

We propose detecting the arrival time of direct signal from two indexes: the value of correlation coefficient and the amplitude of received signal. By setting thresholds for these indexes, the correlation value peak of direct signal can be identified automatically and its correct travel time is obtained. Our proposed algorithm verifies three largest correlation peaks in an order from one with earliest arrival time and identifies one of them as that of a direct signal when the condition is satisfied. In order to determine the thresholds, we used the observation data obtained by using vessel off Ashizuri in June and September 2017. We firstly identified true peak position of direct signal by sight. To provide high recognition accuracy, we determined the condition for our research area: the correlation coefficient is more than 0.25 and signal-to-noise ratio is more than 5.0. The accuracy of identification is expected to be more than 99%.

Since the buoy employs the solar power generation system, there is a concern about the unstable power supply. Thus, we took measures to counter power failure by adding the functionality for automatic restart in power recovery to the signal processing device. We performed operational test for our acoustic ranging system in the pool in October 2017 before the construction on buoy. Both continuous measuring for one week and data transfer from signal processing device to satellite communication unit were successful. We're planning to install the devices on buoy off Ashizuri this year and aiming for stable operation of a continuous observation.