
[JJ] Evening Poster | S (Solid Earth Sciences) | S-EM Earth's Electromagnetism

[S-EM17]Geomagnetism, Paleomagnetism and Rock Magnetism

convener:Nobutatsu Mochizuki(Priority Organization for Innovation and Excellence, Kumamoto University),
Hisayoshi Shimizu(Earthquake Research Institute, University of Tokyo)

Mon. May 21, 2018 5:15 PM - 6:30 PM Poster Hall (International Exhibition Hall7, Makuhari Messe)

We are going to discuss the issues on the magnetic fields of the Earth and planets, paleomagnetism, rock-magnetism, and their applications. This session includes the following topics: (1) observation and analysis of the magnetic fields of the Earth and planets, (2) paleomagnetic field variations obtained from natural and archaeological materials, (3) numerical simulations on the magnetic fields of the Earth and planets, (4) measurements and theories of magnetic properties of rocks, minerals, meteorites and other materials, (5) climate changes and global and local surface tectonics based on the paleomagnetic measurements of rocks and sediments, (6) observations of the magnetic anomalies and the crustal magnetization models of the Earth, planets and satellites, and (7) developments of the experimental method and data analysis. The presentation and discussion will be made in Japanese or English in this session.

[SEM17-P04]A portable, high-frequency susceptometer and its application to rock magnetism

*Kazuto KODAMA¹ (1.Research Center for Knowledge Science in Cultural Heritage, Doshisha University)

Keywords:AC magnetic susceptibility, high frequency, superparamagnetism, frequency dependence

A novel type of magnetic susceptibility meter was developed, for the measurement of high-frequency susceptibility from 10 kHz to 2 MHz. This instrument has high sensitivity, comparable with conventional susceptometers, and is also portable, easy-to-use, and battery-driven, thus making it suitable for use not only in laboratory but also in the field. These features are achieved with the state-of-the-art induction sensor technology and digital front-end processors. The fast measurement time, from several to tens of milliseconds, allows continuous measurements, which would enable scanning the surface of a sample or an outcrop in the field. The high frequency susceptibilities measured with this device provide the information useful for quantifying SP particles more precisely than in the conventional way using the frequency dependence index, or f_d , from two lower frequencies by Bartington's susceptometer. It is also noted that susceptibilities in the high-frequency range over 1 MHz demonstrate anomalous behaviors with some materials. For example, while pure water is weakly diamagnetic below c. 500 kHz, its susceptibility gradually increases toward zero with frequency and, above 500 kHz, it becomes positive, or paramagnetic, and keeps rising slowly until 2 MHz.