

Seismic Wavefield Imaging of Long-Period Ground Motion in the Tokyo Metropolitan Area, Japan

*加納 将行¹、長尾 大道^{2,3}、永田 賢二^{4,5}、伊藤 伸一²、酒井 慎一²、中川 茂樹^{6,2}、堀 宗朗²、平田 直²
*Masayuki Kano¹, Hiromichi Nagao^{2,3}, Nagata Kenji^{4,5}, Shin-ichi Ito², Shin'ichi Sakai², Shigeki Nakagawa^{6,2}, Muneo Hori², Naoshi Hirata²

1. 東北大学大学院理学研究科、2. 東京大学地震研究所、3. 東京大学大学院情報理工学系研究科、4. 産業技術総合研究所 人工知能研究センター、5. 科学技術振興機構 さきがけ研究者、6. 気象庁

1. Graduate School of Science, Tohoku University, 2. Earthquake Research Institute, The University of Tokyo, 3. Graduate School of Information Science and Technology, The University of Tokyo, 4. Artificial Intelligence Research Center, National Institute of Advanced Industrial Science and Technology, 5. Presto, Japan Science and Technology Agency, 6. Japan Meteorological Agency

Long-period ground motions due to large earthquakes can cause devastating disasters, especially in urbanized areas located on sedimentary basins. To assess and mitigate such damage, it is essential to rapidly evaluate seismic hazards for infrastructures, which can be simulated by seismic response analyses that use waveforms at the base of each infrastructure as an input ground motion. The present study reconstructs the seismic wavefield in the Tokyo metropolitan area located on the Kanto sedimentary basin, Japan, from seismograms of the Metropolitan Seismic Observation network (MeSO-net). The obtained wavefield fully explains the observed waveforms in the frequency band of 0.10–0.20 Hz. This is attributed to the seismic wavefield imaging technique proposed by Kano et al. [2017, GJI], which implements the replica exchange Monte Carlo method to simultaneously estimate model parameters related to the subsurface structure and source information. Further investigation shows that the reconstructed seismic wavefield lower than 0.30 Hz is of high quality in terms of variance reduction, which quantifies a misfit in waveforms, but that the variance reduction rapidly worsens in higher frequencies. Meanwhile, the velocity response spectra show good agreement with observations up to 0.90 Hz in terms of the combined goodness-of-fit, which is a measure of misfit in the velocity response spectra. Inputting the reconstructed wavefield into seismic response analyses, we can rapidly assess the overall damage to infrastructures immediately after a large earthquake.

キーワード：地震波動場、レプリカ交換モンテカルロ、マルコフ連鎖モンテカルロ、首都圏地震観測網、データ駆動モデリング

Keywords: seismic wave field, replica exchange Monte Carlo, Markov chain Monte Carlo, MeSO-net, data-driven modeling