

はやぶさ2搭載LIDARアルベド観測における表面地形の影響とその補正 Effect of the surface terrain on the albedo observation by Hayabusa2 LIDAR and its correction

*山田 竜平¹、荒木 博志²、千秋 博紀³、野田 寛大²、並木 則行²、水野 貴秀⁴

*Ryuhei Yamada¹, Hiroshi Araki², Hiroki Senshu³, Hirotomo Noda², Noriyuki Namiki², Takahide Mizuno⁴

1. 会津大学 コンピュータ理工学部、2. 国立天文台、3. 千葉工業大学、4. 宇宙科学研究所

1. The University of Aizu, Department of Computer Science and Engineering, 2. National Astronomical Observatory of Japan, 3. Chiba Institute of Technology, 4. Institute of Space and Astronautical Science

The Japanese asteroid explorer ‘Hayabusa2’ will arrive at the near-Earth C-type asteroid ‘Ryugu’ in this summer. In this mission, we have a plan to apply the laser altimeter (LIDAR) on-board Hayabusa2 to investigate the spatial distribution of normal albedo of Ryugu at the laser wavelength (1064nm). The LIDAR instrument for laser ranging has a function to measure the intensities of transmitted and received pulses. The intensity data can be used to estimate the normal albedo of Ryugu.

In this observation, we have to notice deformation of the returned pulse due to the surface topography. Usually, the returned pulse may be elongated in time and/or attenuated depending on inclination and shape of the reflecting surface. Then, measured intensity of the received pulse can vary with deformation of the returned pulse due to the characteristic of the measurement circuit in the LIDAR even if the normal albedo does not change. We have to correct for the effect to derive accurate albedo.

In this study, we have firstly simulated shape of the deformed returned pulse using possible asteroidal terrain model and feature of the transmitted pulse of the LIDAR. Furthermore, we have investigated the response of the receiver including the measurement circuit for the simulated pulses using LIDAR-EM (Engineering Model). In the experiment, the laser transmitter developed in Chiba Institute of Technology was applied to produce the input pulse. In this presentation, we will report the results of the numerical simulation and the experiment. Then, we discuss how we can correct for the effect of the surface terrain on the measured intensity data of the received pulse.

キーワード：レーザ高度計、アルベド、C型小惑星、はやぶさ2

Keywords: LIDAR, albedo, C-type asteroid, Hayabusa2