

## 地熱流体パス抽出を目的とした超高解像度DEMとハイパースペクトル衛星画像による亀裂・鉱物分布解析

### Fracture and mineral distribution analysis using hyper-resolution DEM and hyperspectral satellite imagery for detecting geothermal fluids paths

\*久保 大樹<sup>1</sup>、権守 宏明<sup>1</sup>、Naftali Hawu Hede Arie<sup>2</sup>、Heriawan Mohamad Nur<sup>2</sup>、Iskandar Irwan<sup>2</sup>、小池 克明<sup>1</sup>、Notosiswoyo Sudarto<sup>2</sup>

\*Taiki Kubo<sup>1</sup>, Hiroaki Gonnokami<sup>1</sup>, Arie Naftali Hawu Hede<sup>2</sup>, Mohamad Nur Heriawan<sup>2</sup>, Irwan Iskandar<sup>2</sup>, Katsuaki Koike<sup>1</sup>, Sudarto Notosiswoyo<sup>2</sup>

1. 京都大学大学院工学研究科、2. バンドン工科大学

1. Graduate School of Engineering, Kyoto University, 2. Bandung Institute of Technology

From criteria of power output and temporal stability, geothermal is the most promising renewable energy for electrical generation. However, high introduction cost for geothermal power generation, in particular the cost for exploration to identify the geothermal reservoir is a main issue against the plan. Development of more accurate geothermal-resource exploration is necessary for enhancement of geothermal energy use. Detection of geothermal fluids paths including water and steam from geothermal reservoir is a major target in the exploration stage. Topographic analysis is one of the effective methods for the detection. Thus, we have generated a hyper-resolution DEM (HR-DEM) of the Wayang Windu Geothermal Field (WWGF), situated in West Java, Indonesia using UAV. HR-DEM with high spatial resolution (0.5 m) covers an area of 5 km (E-W) by 10 km (N-S) in WWGF. The lineament density map of WWGF was produced by a topographic analysis through HR-DEM. Moreover, spatial distributions of geothermal alteration minerals such as alunite, calcite, and kaolinite were mapped from an image processing of hyperspectral satellite image, Hyperion. A combination of the lineament and mineral distributions specified highly permeable zones in which the fractures and geothermal alteration minerals were concentrated. The location of high radon concentration by in-situ measurements correspond well with these estimated permeable zones. Therefore, the integrated analysis is expected to increase the identification accuracy of fluid paths and clarify the geothermal system in WWGF. This research is supported by JST and JICA through Science and Technology Research Partnership for Sustainable Development (SATREPS).

キーワード：変質鉱物、数値標高モデル、地熱貯留層、ハイパースペクトル衛星画像、リニアメント

Keywords: alteration mineral, digital elevation model, geothermal reservoir, hyperspectral satellite image, lineament