

石英質岩石の中速摩擦強度の支配要因

Mechanism controlling the frictional strength of quartz rocks at intermediate slip rates

*金川 久一¹、杉田 明日郁²、高橋 美紀³、澤井 みち代¹

*Kyuichi Kanagawa¹, Asuka Sugita², Miki Takahashi³, Michiyo Sawai¹

1. 千葉大学理学研究院、2. 千葉大学理学部、3. 産業技術総合研究所活断層・火山研究部門

1. School of Science, Chiba University, 2. Faculty of Science, Chiba University, 3. Research Institute of Earthquake and Volcano Geology, Geological Survey of Japan

Frictional strength of quartz rocks is known to be extraordinary low at subseismic slip rates ranging from 1 mm/s to 10 cm/s, which has been ascribed to the hydration of comminuted amorphous silica, i.e., silica gel. In order to testify this hypothesis, we conducted rotary-shear friction experiments on intact agate or silica gel gouge at a normal stress of 1.5 MPa and slip rates (V) ranging from 1 mm/s to 10 cm/s. We also measured temperature (T) adjacent to the slip surface or the gouge layer during the experiments.

Steady-state friction coefficient of agate μ_{ss} was ≈ 0.6 at $V = 1$ mm/s, ≈ 0.5 at $V = 7$ mm/s, and ≤ 0.1 at $V = 10$ cm/s. T was $\approx 25^\circ\text{C}$ at $V = 1$ mm/s, $\approx 30^\circ\text{C}$ at $V = 7$ mm/s, and up to 85°C at $V = 10$ cm/s, but the actual temperature along the slip surface must have been much higher. μ_{ss} of silica gel gouge was ≈ 0.7 at $V = 1$ mm/s, 0.4–0.5 at $V = 7$ mm/s, and ≤ 0.2 at $V = 10$ cm/s. T was $25\text{--}28^\circ\text{C}$ at $V = 1$ mm/s, $30\text{--}37^\circ\text{C}$ at $V = 7$ mm/s, and $80\text{--}100^\circ\text{C}$ at $V = 10$ cm/s, but again, the actual temperature in the gouge layer must have been much higher.

Thus our results show that agate or silica gel exhibits weakening with increasing T , and that the presence of silica gel does not reduce the frictional strength when T is not high enough. Shear strength of quartz rocks is high so that significant amount of frictional heat would be produced at asperity contacts even at $V \approx 1$ cm/s, which must be responsible for weakening of quartz rocks at intermediate slip rates.

キーワード：めのう、シリカゲル、摩擦強度、中速

Keywords: agate, silica gel, frictional strength, intermediate slip rates