

Molecular Dynamics Study on Coal Matrix Swelling Characteristics by CO₂, N₂, and CO₂-N₂ Mixture

*Jinrong Cao¹, Yunfeng Liang¹, Yoshihiro Masuda¹, Ziqiu Xue², Toshifumi Matsuoka³

1. Department of Systems Innovation, The University of Tokyo, 2. Research Institute of Innovative Technology for the Earth, 3. Emeritus Professor, Kyoto University

CO₂ sequestration in coal seams is an economically viable option to reduce carbon emissions. Coalbed methane (CBM) is CH₄ stored in the nanopores of the coal matrix. CO₂ Enhanced CBM (CO₂-ECBM) is considered prospective technology that can not only meet the increasing world energy resource demands but also ease greenhouse gas emissions by injecting CO₂ into the coal seams. The injected CO₂ is capable of promoting CH₄ production. In the meantime, coal seams possess huge potentials for geological CO₂ sequestration. However, the replacement process of CH₄ in the coal matrix and the swelling/shrinkage of the coal matrix are poorly understood. Therefore, in this work, the molecular dynamics simulation study is presented considering the recovery of CH₄ in the coal matrix and swelling of the coal matrix using CO₂, N₂, and CO₂-N₂ mixture, three different displacement schemes.

We quantify the amount by monitoring the density profiles. The results show that recovery of CH₄ and swelling of the coal matrix are different in three displacement schemes. The use of CO₂ injection obtained the highest recovery of CH₄ inside the coal matrix. Meanwhile, coal matrix swelling is also quite severe. On the other hand, the use of CO₂-N₂ mixture injection yielded an increase of CH₄ recovery as compared with the case of injecting pure N₂. The coal matrix swelling is not severe. Also, there might be coal matrix shrinkage during the pure N₂ displacement case. This work should shed light on the swelling of the coal matrix and recovery of CH₄ during CO₂, N₂, and CO₂-N₂ mixture injection in coal seams.