

Collaboration between meteorology and wind engineering on development of Japanese Enhanced Fujita Scale

*Yoshinobu Tanaka¹, Yukio Tamura^{2,3}, Hiroshi Niino⁴, Masaru Ito⁵, Yasuo Okuda⁶, Hitomitsu Kikitsu⁷, Fumiaki Kobayashi⁸, Hiroyasu Sakata⁹, Satoru Suzuki¹⁰, Yoshinori Shoji¹¹, Junji Maeda¹²

1. Japan Meteorological Agency, 2. Tokyo Polytechnic University, 3. Beijing Jiaotong University, 4. University of Tokyo, 5. Nihon Sekkei, Inc., 6. Building Research Institute, 7. National Institute for Land and Infrastructure Management, 8. National Defense Academy, 9. Tokyo Institute of Technology, 10. Forestry and Forest Products Research Institute, 11. Meteorological Research Institute, 12. Kyushu University

Tornadoes are infrequent, small-scale brief phenomena whose development is difficult to identify with ordinary weather observation network resources. It is necessary for identification of such small-scale phenomena to investigate the tornado damage in order to estimate the phenomenon type and its intensity. The Japan Meteorological Agency (JMA) dispatches the JMA Mobile Observation Team (JMA-MOT) to tornado disaster sites, and they investigate damage for identifying the information on the phenomenon and its intensity scientifically (referred to here as rating). The Fujita scale has conventionally been used to rate tornado intensity.

The Fujita scale was developed in 1971 by Dr. Fujita at the University of Chicago and has been commonly adopted in the United States and worldwide because it can easily rate tornado intensity by classifying it into six categories, F0~F5, based on damage to buildings and other structures.

But the Fujita Scale has a limit to the accuracy of rating because of some issues: correspondence between damage descriptions and wind speeds has not been adequately verified, the damage indicators (DI) are limited, and so on. In response to these issues, the Enhanced Fujita scale, which provided the wind speed estimation based on 28 DIs distributed widely in the United States and their degrees of damage (DODs), was developed in 2006, and was adopted by the National Weather Service in 2007.

In Japan, after the tornado on May 2012 which caused severe damage in several cities, such as Tsukuba in Ibaraki prefecture, various measures were proposed by not only JMA but also by whole Japanese government ministries and agencies. As a part of these measures, the Japanese Enhanced Fujita scale, whose DIs were defined from buildings and other structures commonly found in Japan, was formulated on the basis of cutting-edge expertise in wind engineering with reference to the Enhanced Fujita Scale in the United States.

Based on the examination of “the Advisory Committee for Tornado Intensity Rating” (chair: Yukio Tamura, professor emeritus, Tokyo Polytechnic University) consisting of wind engineering, architecture, forestry and meteorology experts, JMA has developed and released “Guidelines for the Japanese Enhanced Fujita Scale” in Dec 2015.

The characteristics of the Japanese Enhanced Fujita scale are as follows: (1) Introduction of damage indicators and degrees of damage corresponding to buildings and other structures commonly found in Japan; (2) Determination of wind speeds (rounded to multiples of 5m/s) corresponding to damage indicators and degrees of damage; (3) Unification of wind speeds into three-second average values; (4) Correspondence of wind speed ranges to classes (JEF0~JEF5) in consideration of statistical continuity with the Fujita scale. These advantages enable more accurate estimation of wind speed than rating using the

conventional Fujita scale and it also became easy to compare tornado cases with ones in the past.

The formulation of the guidelines was examined with reference to the expertise of many researchers participating in a special research project titled Cooperative Study on a New Scale for Rating Tornadoes in Japan (research representative: Yasuo Okuda, Director, Department Structural Engineering, Building Research Institute) conducted by the Wind Engineering Joint Usage/Research Center with funding from the Ministry of Education, Culture, Sports, Science and Technology. This formulation could not be achieved without the promotion of research by close collaboration between wind engineering and meteorology in this project. It also produced DIs and DODs to be applied to wind speed rating without specialized knowledge of engineering, considering JMA staffs survey destructiveness at disaster sites.

JMA has implemented Japanese Enhanced Fujita scale from Apr 2016, and rated 44 cases (tornadoes, downbursts and other hazardous winds) until the end of Dec 2016. The rating results are opened on tornado database of JMA web page. 30 types of buildings and other structures are used as DIs now, but as the number of rating cases at disaster sites increased during the implementation, it has become clear that new DIs and/or DODs need to be added. In response to these issues, the related research keeps on being carried out under the collaboration between wind engineering and meteorology in order to make the Japanese Enhanced Fujita Scale easier to use.

Keywords: Tornado, Wind Disaster, Damage Survey, Wind Engineering, Interdisciplinary cooperation