

Transport of Colloidal Particles in Saturated Toyoura Sand: Effects of Flow Rate on Importance of Electrostatic Repulsion

*杉本 卓也¹、濱本 昌一郎¹、西村 拓¹、足立 泰久²、小林 幹佳²

*Takuya Sugimoto¹, Shoichiro Hamamoto¹, Taku Nishimura¹, Yasuhisa Adachi², Motoyoshi Kobayashi²

1. 東京大学大学院農学生命科学研究科、2. 筑波大学生命環境系

1. Graduate School of Agricultural and Life Sciences, The University of Tokyo, 2. Faculty of Life and Environmental Sciences, University of Tsukuba

There are substantial colloidal particles such as clay minerals and metal oxides in soil environments. Such colloidal particles have been considered as a potential carrier of contaminants in vadose zone and aquifer, due to their surface charges and high specific surface area. Therefore, understanding the transport mechanisms of colloidal particles in soils is essential to predict the fate of the contaminants in the environments. In this study, we analyze deposition rate coefficients of polystyrene latex particles with a diameter of 1 μm in a column packed with Toyoura sand with an average diameter of 0.274 mm as a function of NaCl concentration at three different flow rates. The concentration of the colloids in the effluent was quantified using a spectrometer photometer. The experimental results showed that the deposition rate coefficients of the colloids increased with increasing NaCl concentrations and reached a plateau above a certain NaCl concentration, called the critical deposition concentration (CDC). The CDCs shifts to higher salt concentrations with increasing injected flow rates. We show that this experimental trend can be captured by a simplified model including physico-chemical interactions based on the DLVO theory.

キーワード：コロイド粒子、輸送、多孔質媒体、イオン強度、流量

Keywords: Colloidal particles, Transport, Porous media, Ionic strength, Flow rate