

Automatic determination of Upper Hybrid Resonance Frequencies by Convolutional Neural Network.

*松田 昇也¹、長谷川 達人²、熊本 篤志³、土屋 史紀³、笠原 禎也⁴、三好 由純⁵、笠羽 康正³、松岡 彩子¹

*Shoya Matsuda¹, Tatsuhito Hasegawa², Atsushi Kumamoto³, Fuminori Tsuchiya³, Yoshiya Kasahara⁴, Yoshizumi Miyoshi⁵, Yasumasa Kasaba³, Ayako Matsuoka¹

1. 宇宙航空研究開発機構 宇宙科学研究所、2. 福井大学、3. 東北大学、4. 金沢大学、5. 名古屋大学 宇宙地球環境研究所
1. Institute of Space and Astronautical Science/Japan Aerospace Exploration Agency, 2. University of Fukui, 3. Tohoku University, 4. Kanazawa University, 5. ISEE, Nagoya University

Electron number density is a key parameter for discussions of plasma wave generation/propagation, and wave-particle interaction in the inner magnetosphere. The High Frequency Analyzer (HFA) is a subsystem of Plasma Wave Experiment (PWE) aboard Arase [Kasahara et al. (2018), Kumamoto et al. (2018), Miyoshi et al. (2018)]. The HFA measures electric field spectra in a frequency range from 10 kHz to 10 MHz, which covers a typical frequency range of Upper Hybrid Resonance (UHR) frequency in the inner magnetosphere. Kumamoto et al. (2018) proposed the semiautomatic method for the identification of UHR frequency by computer and a human operator. However, it takes a enormous effort of a human operator.

We propose an automatic determination system of UHR frequency by machine learning. Machine learning is a technique in the field of artificial intelligence to give computers the ability to learn with data. In this study, we defined a task of UHR frequency determination as supervised regression that a computer estimates UHR frequencies using the dataset composed of electric field dynamic spectra with correct UHR frequency labels. We adopted Convolutional Neural Network (CNN) as a machine learning algorithm. In this study, we introduce our machine learning approach and initial results for determining UHR frequency from electric field spectra observed by PWE/HFA.

キーワード：あらせ衛星、UHR周波数、機械学習

Keywords: Arase satellite, UHR frequency, Machine learning