

Validation of High-energy electron detector simulator for the HEP instruments onboard Arase

*Takefumi Mitani¹, PARK INCHUN², Tomoaki Hori², Taku Namekawa^{1,3}, Kazushi Asamura¹, Takeshi Takashima¹, Satoshi Kasahara³, Satoshi Kurita², Mariko Teramoto², Nana Higashio¹, Yoshizumi Miyoshi², Iku Shinohara¹

1. Japan Aerospace Exploration Agency, Institute of Space and Astronautical Science, 2. Institute for Space-Earth Environmental Research, Nagoya Univ., 3. The university of Tokyo

The high-energy electron experiments (HEP) onboard the Arase satellite detects 70 keV–2 MeV electrons and generates a three-dimensional velocity distribution for these electrons in every period of the satellite's rotation. Electrons are detected by two instruments, namely, HEP-L and HEP-H, which differ in their geometric factor (G-factor) and range of energies they detect. HEP-L detects 70 keV–1 MeV electrons and its G-factor is $9.3 \times 10^{-4} \text{ cm}^2 \text{ sr}$ at maximum, while HEP-H observes 0.7 MeV–2 MeV electrons and its G-factor is $9.3 \times 10^{-3} \text{ cm}^2 \text{ sr}$ at maximum. The instruments utilize silicon strip detectors and application-specific integrated circuits to readout the incident charge signal from each strip.

In order to deduce the distribution of incident electrons from the direction and energy detections in orbit, we have developed a detector simulator using the Geant4 toolkit. Especially contamination due to high energy particles must be considered quantitatively. We have also been working on electron beam experiments using HEP detector modules which are almost the same as the flight model in order to compare detailed simulations and experimental data.

We will present a comparison between results from the electron beam experiments and those from the detector simulator. And we will discuss its influence on the interpretation of the observational data obtained in orbit.

Keywords: high-energy electron, Arase, Geant4