地震時に断層破砕帯における粉粉になった断層破砕物の貫入と天水・海水 を含む流体の流動

Repeated coseismic injection of pulverized fault rocks and infiltration of fluids including meteoric and sea-waters within fault damage zones

- *林 愛明¹
- *Aiming Lin¹
- 1. 京都大学大学院理学研究科地球惑星科学専攻地球物理学教室
- 1. Department of Geophysics, Graduate School of Science, Kyoto University

In the past decades, increasing geological evidence has emerged that faults and shear zones within the middle to upper crust play a crucial role in controlling the architecture of crustal fluid migration and seismic faulting process. It is also well known that fluid can be released by dehydration reaction caused by seismic frictional heating during large earthquakes within both intracontinental faults and subduction zones that contain abundant hydrous minerals (Lin et al., 2003, 2013). Such rapid dehydration reaction would induce a sudden increase in fluid pressure that would simultaneously act to reduce the effective normal stress and markedly weaken the dynamic strength of seismogenic faults during seismic faulting, thereby facilitating seismic slip during large earthquakes. For an integrated multidisciplinary study on the assessment of activity of active faults involving active tectonics, rock-fluid interactions, geochemistry and geochronology of active fault and seismogenic fault zones, recently, a new project of "Drilling into Fault Damage Zone" has being conducted by Kyoto University on the Nojima Fault again after 20 years of the 1995 Kobe earthquake.

In this presentation, I will review the previous studies and report the recent progresses on the fluid infiltration concerning with coseismic faulting and recent activity on two seismogenic faults that recently triggered the large earthquakes, one from the active faults of the Longmen Shan Thrust Belt that triggered the 2008 M_w 7.9 Wenchaun earthquake in the Sichuan basin, China, the other is the Nojima Fault that triggered the 1995 M., 7.2 Kobe earthquake. Circulating fluids deposit fine-grained sediments including clay and carbonate material and pulverized rock materials into cracks within the fault zones. Such crack-fill fine-grained materials, calcite veins, and oxidized/weathered open cracks have well been observed in the drill cores, from both the Nojima Fault and the active faults of the Longme Shan Thrust Best. 3D micro-X-ray scanning data and powder X-ray diffraction analyses show that the fault core zone contains a numerous of veinlets which are composed of fine-grained materials, carbonate material and clay minerals. Isotopic analyses of carbonate material within the fine-grained materials and calcite veins reveal that the calcite veins are sourced from typical meteoric and seawater. ¹⁴C dating ages of 10 calcite vein samples range from 35.0 to 58.4 kyr B.P. Geological, petrological, stable isotopic, and ¹⁴C data suggest that these crack-fill fine-grained materials and calcite veins and brown open cracks were developed by the repeated infiltration of O₂- and CO₂-bearing meteoric and seawater downward into the deep fault zone during the last 35–60 kyr. We propose a seismic fault suction-pumping model to interpret the infiltration of subsurface waters being carried down into the deep fault zone by rapid potential change during episodes of seismic faulting.

References

Lin et al. (2003). Repeated coseismic infiltration of meteoric and seawater into deep fault zones: a case study of the Nojima fault zone, Japan. Chem. Geol., 202, 139-153.

Lin et al. (2013). Coseismic dehydration of serpentinite during large earthquakes: Evidence from high-velocity friction experiments. Chemical Geology, 344, 50-62.

キーワード:地震断層岩の注入脈、地震時の断層帯の流体流動、地震断層の流体吸引モデル
Keywords: coseismic injection of pulverized fault rocks, coseismic infiltration of fluid, seismic fault suction-pumping model