Viscosity of CO₂-bearing sodium aluminosilicate melt at high pressure

*鈴木 昭夫¹ *Akio Suzuki¹

1. 東北大学大学院理学研究科地学専攻

1. Department of Earth Science, Graduate School of Science, Tohoku University

Viscosity is one of the important transport properties controlling the migration of magma in the Earth's interior. Experimental and geochemical studies showed that magma in the deep interior was generated in the presence of CO_2 . However, our knowledge on the effect of CO_2 on the viscosity of magma (silicate melt) is still insufficient. Here we report the viscosity of sodium aluminosilicate melt with jadeite composition containing 0.5 wt% of CO_2 under high pressure. Viscosity was measured by the falling sphere method by using X-ray radiography image. Experiments were carried out using the MAX-III apparatus installed at the station NE7A of PF-AR synchrotron radiation facility in KEK (High Energy Accelerator Research Organization), Tsukuba, Japan. Viscosity was calculated using the Stokes equation with the correction of wall effect. Viscosity measurements were carried out up to 2.4 GPa. We observed that viscosity of the CO_2 -bearing melt was one order of magnitude lower than those of CO_2 -free jadeite melt.

キーワード:マグマ、揮発性元素、二酸化炭素、マントル、高圧、放射光

Keywords: magma, volatile elements, carbon dioxide, maltle, high pressure, synchrotron radiation