

地球核条件下にレーザー衝撃圧縮された鉄合金融体の音速と密度の関係 Sound velocity and density of liquid iron alloys under Earth's core pressures by laser-shock compression

*境家 達弘¹、近藤 忠¹、寺崎 英紀¹、重森 啓介²、弘中 陽一郎²

*Tatsuhiko Sakaiya¹, Tadashi Kondo¹, Hidenori Terasaki¹, Keisuke Shigemori², Yoichiro Hironaka²

1. 大阪大学大学院理学研究科宇宙地球科学専攻、2. 大阪大学レーザーエネルギー学研究センター

1. Graduate School of Science, Osaka University, 2. Institute of Laser Engineering, Osaka University

Sound velocity at Earth's core conditions are one of the most important physical properties in Earth science because it can be directly compared with the seismological Earth model (PREM: Preliminary Reference Earth Model) [1]. The composition of solid inner core is estimated from the comparison of the model [1] and the extrapolation of sound velocities as a function of density of iron and iron alloys obtained by the static compression experiment [2, 3]. Birch's law, a linear sound velocity-density relation [4], is used to extrapolate sound velocities to densities in the core condition. On the other hand, the composition of liquid outer core is estimated from the partitioning and solubility data in the inner core boundary condition for the composition of solid core. There has been some works for the sound velocity of iron and iron alloys on the Earth's core condition by dynamic techniques using explosive [5], gas gun [5-9], and laser [10-12]. Huang et al. estimated that the outer core composition is Fe with 0.5 wt.% O and 9.5 wt.% S by the comparison of PREM and sound velocities of Fe-S-O system [9]. In this study, we measure the sound velocity and density of liquid iron alloys by shock-compression method using high-power laser.

We conducted shock-compression experiments using a High Intensity Plasma Experimental Research (HIPER) system at the GEKKO-XII laser irradiation facility [13] at the Institute of Laser Engineering, Osaka University. The samples were Fe-Ni alloys, Fe-Si alloys, and pyrrhotite. The sound velocities and densities of shock-compressed iron alloys using the high-power laser were measured by x-ray radiography [10-12] at pressures up to 1000 GPa.

Part of this work was performed under the joint research project of the Institute of Laser Engineering, Osaka University and supported by JSPS KAKENHI Grant Number JP16K05541.

References

- [1] A. M. Dziewonski and D. L. Anderson, *Phys. Earth Planet. Inter.* 25, 297-356 (1981).
- [2] J. Badro et al., *Earth Planet. Sci. Lett.* 254, 233-238 (2007).
- [3] G. Fiquet et al., *Phys. Earth Planet. Inter.* 172, 125-129 (2009).
- [4] F. Birch, *Geophys. J. R. Astron. Soc.* 4, 295-311 (1961).
- [5] J. M. Brown and R. G. McQueen, *J. Geophys. Res.* 91, 7485-7494 (1986).
- [6] J. H. Nguyen and N. C. Holmes, *Nature* 427, 339-342 (2004).
- [7] J. W. Shaner et al., *Shock Waves in Condensed Matter*, 135-138 (1988).
- [8] H. Huang et al., *J. Geophys. Res.* 116, B04201 (2010).
- [9] H. Huang et al., *Nature* 479, 513-516 (2011).
- [10] K. Shigemori et al., *Eur. Phys. J. D* 44, 301-305 (2007).
- [11] K. Shigemori et al., *Rev. Sci. Instrum.* 83, 10E529 (2012).
- [12] T. Sakaiya et al., *Earth Planet. Sci. Lett.* 392, 80-85 (2014).
- [13] C. Yamanaka et al., *Nucl. Fusion* 27, 19-30 (1987).

キーワード：音速、衝撃圧縮、鉄合金、地球核、バーチ則

Keywords: Sound velocity, Shock compression, Iron alloy, Earth's core, Birch's law